

PVC MULTI-CARTRIDGE FILTERS

MODEL	CONNECTION	CARTRIDGE QTY	CARTRIDGE LENGTH	DIMENSIONS (cm)	WEIGHT (kg)	FLOW RATE (m ³ /h)			
						1μ	5μ	10μ	25μ
PVC 520-AYB	DN50	5	20"	30 x 30 x 72	13	5	10	15	20
PVC 530-AYB	DN50	5	30"	30 x 30 x 100	14,5	7,5	15	22,5	23
PVC 540-AYB	DN50	5	40"	30 x 30 x 120	16,5	10	20	23	23
PVC 920-AYB	DN80	9	20"	40 x 40 x 72	21	9	18	27	36
PVC 930-AYB	DN80	9	30"	40 x 40 x 100	26	13,5	27	40,5	54
PVC 940-AYB	DN80	9	40"	40 x 40 x 120	31	18	36	54	55

Operating Pressure: 5 bar (Max) Body: PVC Material Micron Rating: 1 - 25 Micron

STAINLESS STEEL MULTI-CARTRIDGE FILTERS

MODEL	CONNECTION	CARTRIDGE QTY	CARTRIDGE LENGTH	DIMENSIONS (cm)	WEIGHT (kg)	FLOW RATE (m ³ /h)			
						1μ	5μ	10μ	25μ
ACF 320	2"(DN50)	3	20"	375 x 426 x 954	19	3	6	9	12
ACF 330	2"(DN50)	3	30"	375 x 426 x 1200	22	4,5	9	13,5	18
ACF 340	2"(DN50)	3	40"	375 x 426 x 1250	24	6	12	18	23
ACF 520	2"(DN50)	5	20"	425 x 470 x 973	23	5	10	15	20
ACF 530	2"(DN50)	5	30"	425 x 470 x 1223	27	7,5	15	22,5	23
ACF 540	2"(DN50)	5	40"	425 x 470 x 1473	32	10	20	23	23
ACF 830	2 1/2"(DN65)	8	30"	435 x 440 x 1235	37	12	24	36	40
ACF 840	2 1/2"(DN65)	8	40"	435 x 440 x 1485	44	16	32	40	40
ACF 1230	3"(DN80)	12	30"	490 x 485 x 1238	49	18	36	54	55
ACF 1240	3"(DN80)	12	40"	490 x 485 x 1538	58	24	48	55	55
ACF 1640	4"(DN100)	16	40"	595 x 600 x 1550	82	32	64	94	94
ACF 2740	5"(DN125)	27	40"	790 x 790 x 1574	115	54	108	140	140

Operating Pressure: 7 bar (Max) Body: AISI 304 Stainless steel Micron Rating: 1 - 25 Micron



SPUN FILTERS



MODEL PVC5



MODEL PVC9



MODEL ACF

AQUALINE PVC BAG FILTER SYSTEMS

MODEL	CONNECTION	FLOW RATE (m ³ /h)	DIMENSIONS (mm)	WEIGHT (kg)
PVC732 AYB	2" (DN50)	10	400 x 420 x 1180	18

SPARE BAG FILTERS

MODEL	DIMENSIONS (mm)	MICRON RATING
7" - 32"	170 x 820	5 - 10 - 25 - 50 - 100 - 200 Micron

STAINLESS STEEL BAG FILTERS

AQUALINE SS304

MODEL	CONNECTION	FLOW RATE (m ³ /h)	DIMENSIONS (mm)	WEIGHT (kg)
ABF732	2" (DN50) GEAR	10	430 x 440 x 1075	32
ABF3 x 732	3" (DN80) GEAR	30	625 x 660 x 1180	100

SEPARATOR FILTERS

MODEL	CONNECTION	FLOW RATE (m ³ /h)	DIMENSIONS (mm)	WEIGHT (kg)
SS304 STAINLESS STEEL / ST-37 CARBON STEEL (EPOXY PAINTED)				
AQUALINE SP 100	1/2" (DN15)	1-1,5	780 x 176 x 140	6
AQUALINE SP 150	3/4" (DN20)	2-7,5	780 x 176 x 140	6
AQUALINE SP 175	1" (DN25)	6,5-11	775 x 208 x 168	7,7
AQUALINE SP 200	1 1/4" (DN32)	10-16	775 x 223 x 168	9
AQUALINE SP 250	1 1/2" (DN40)	14,5-18	775 x 223 x 168	10
AQUALINE SP 350	2" (DN50)	17-24.5	1185 x 450 x 410	18,5
AQUALINE SP 450	2 1/2" (DN65)	22-35	1185 x 450 x 410	19
AQUALINE SP 600	3" (DN80)	33,5-66	1430 x 520 x 470	29,3
AQUALINE SP 800	4" (DN100)	64-110	1720 x 540 x 485	50,5

Operating Pressure: 6-8 bar (Max.)

Drain Line: For all models 1"

Micron Range: 70-110 Micron



PVC BAG FILTERS



SPARE BAG FILTERS



HONEYWELL
PURGE VALVE



SP100 - SP250



SP350 - SP800



SS304 BAG FILTER